



# // DATA SHEET

# WEIGHTS & DIMENSIONS ON TRAILER WEIGHT (LBS) 55,000 N/A

576 L x 102 W x 157.5 H

# **PERFORMANCE**

- 560 HP
- 3,500,000 SCFD flow rate (max)

### COMPRESSOR

- · 4 throw/3 stage configurable air cooled compressor
- 1250 psig max pressure

# DRIVER

- 18.8 L gas compression engine rated at 420 HP @ 1800 RPM
- Six Cylinder Turbocharged-Aftercooled 1150 Cubic Inches
- · Electronic ADEM A4 engine control system
- · Industrial grade exhaust silencer
- · Mechanical governor controlled
- Standard 24V starter w/ battery/alternator system

# COOLER

· Forced draft, multiple fan, vertical discharge

# PROCESS PIPING & VESSELS

- Hard piping for process gas
- Scrubbers and/or bottles on suction, 1st-3rd stage suction and discharge
- · Automatic liquid level control system
- High level shutdownsm
- · Manual drain valves

## SAFETY

DIMENSIONS (IN)


- Pressure relief valves (PRV) on all three stages, fuel gas and blowcase.
- · PRV relief piping to atmosphere above head height

## PACKAGING

- Environmental rails around perimeter coming to six drain points
- · Trailer mounted for mobility

# **CONTROL SYSTEM**

• FW Murphy Centurion C5



MAGNITUDE OF RELEASE