





### **PERFORMANCE**

- 67 HP
- · 250,000 SCFD flow rate (max)

#### COMPRESSOR

- (1) 4 throw/4 stage air-cooled, direct drive continuous duty compressors
- 1440 psig max pressure

#### **SAFETY**

- Pressure safety valves for inlet system and each stage of compression
- $\bullet$  Independent fast response overpressure ESD valve
- · Manual ball valve at inlet
- · Check valve at compressor discharge
- · Unloaded start system
- · Automatic interstage condensate drains

### INLET GAS SYSTEM

- · 2" piping
- First stage scrubber: 16" OD x 30" S/S x 1000 PSIG MAWP @ 150F/-20F
- Level control switch
- Pressure safety valve
- Liquid level gauge
- Temperature and pressure transmitters



STATE OF			
	WEIGHTS & DIMENSIONS	ON FLAT BED	
	WEIGHT (LBS)		
	DIMENSIONS (IN)	120 L X 96 W X 78.5 H	

\* DIMENSIONS REFER TO UNIT ONLY / DOES NOT INCLUDE TRUCK

#### DRIVER

• (1) 4.5L natural gas engine rated at 67 HP @ 1800RPM

#### **PACKAGING**

- · Unit assembled on truck flatbed with weather enclosure
- · Multiple access doors

## **CONTROL SYSTEM**

• FW Murphy Centurion C5 control panel

# STRAIGHT-LINE™ PERFORMANCE

